











Ward stretcher fixed height 2 sections with constant brake

The base is composed by two removable sections made of zinc coated steel hooked to plastic supports.

The four holes are equipped with holes as push handle and for placing accessories, and with shockresistant no trace bumpers.

The head side is equipped with supports for drainage bags and bottle holder.

The backrest is moved by a bilateral lever and assisted by a pneumatic spring.

Light structure realized with steel profiles of high thickness and varnished with epoxy powders. At the base wheels \emptyset 200 mm, one wivelling, one directional and fixed, 2 swivelling at head side with spring brake.

The brake is always inserted; to unlock it is sufficient to operate on the handle on the head side.

TECHNICAL DETAILS

Overall dimensions cm 204x70x78h
Base dimensions cm 198 x 58
Backrest inclination from 0° to 80°
Base height cm 78
Castors Ø 200 mm
Weight kg 48
Safe working load kg. 170
Height of the side rails from the sprung base cm 28
Medical device class I following Dir. 93/42 CEE





BZ1520-STEEL BOTTLE HOLDER



BZ1525-PAPER HOLDER FOR STRETCHERS



RA0070-STAINLESS STEEL SUPPORT FOR URINE AND DRAINAGE BAGS



BZ1545-OVERPRICE FOR PLASTIC WHEELS, ONE ANTISTATIC WHEELS



BZ1524-I.V. STAND,2 HOOKS, ADJUSTABLE HEIGHT



BZ1518-MONITOR SHELF FOR STRETCHERS



BZ1535-PUSHING HANDLE



BZ1501-ANTISTATIC MATTRESS FOR STRETCHERS WITH SIDE RAILS BZ1604



BZ1604-FLAP SIDE RAILS FOR STRETCHERS BS15..-BS16..



BZ1606-HOLDER BASKET MADE OF VARNISHED STEEL